

A N T O R N I O D E T O R R E S

HITEK MENSWEAR

HOW TO MEASURE

THE JACKET'S CHEST WIDTH



STEP 1. LAY THE JACKET OUT

LAY THE JACKET COMPLETELY BUTTONED FLAT ON A TABLE FACE UP WITH THE COLLAR UP AND THE ARMS POSITIONED UPWARD.

USE YOUR HANDS TO GENTLY EXTEND & FLATTEN OUT THE EXCESS FABRIC TO MAKE IT FLAT AND SMOOTH



STEP 2. MEASURE ACROSS THE JACKET CHEST

STARTING AT THE LOWERMOST POINT OF THE LEFT ARMHOLE, MEASURE ACROSS TO THE SAME POINT ON THE RIGHT ARMHOLE

HOW TO MEASURE

THE JACKET'S WAIST WIDTH



STEP 1. LAY THE JACKET OUT

LAY THE JACKET COMPLETELY BUTTONED FLAT ON A TABLE FACE UP WITH THE COLLAR UP AND THE ARMS POSITIONED UPWARD.

USE YOUR HANDS TO GENTLY EXTEND & FLATTEN OUT THE EXCESS FABRIC TO MAKE IT FLAT AND SMOOTH



STEP 2. MEASURE ACROSS THE WAIST

STARTING AT THE LEFT EDGE OF THE JACKET'S WAISTLINE, MEASURE ACROSS WITH MIDWAIST POINT JUST BELOW THE 1ST BUTTON

HOW TO MEASURE

THE JACKET'S SHOULDER WIDTH



STEP 1. LAY THE JACKET OUT

LAY THE COMPLETELY BUTTONED JACKET FLAT ON A TABLE FACE DOWN WITH THE COLLAR DOWN AND ARMS POSITIONED DOWNWARD.

USE YOUR HANDS TO GENTLY EXTEND AND FLATTEN OUT EXCESS FABRIC.



STEP 2. MEASURE ACROSS

BEGINNING ON THE LEFT SIDE, WHERE THE TOP OF THE ARMHOLE SEAM MEETS THE SHOULDER FOLD, MEASURE ACROSS, STOPPING AT THE SAME POINT AT THE RIGHT SIDE OF THE JACKET.

HOW TO MEASURE

THE JACKET'S SLEEVE LENGTH



STEP 1. LAY THE JACKET OUT

LAY THE COMPLETELY BUTTONED JACKET FLAT ON A TABLE FACING UPWARDS WITH THE COLLAR DOWN AND ARMS STRAIGHTENED TO THEIR NATURAL POSITION.

USE YOUR HANDS TO GENTLY EXTEND AND FLATTEN OUT EXCESS FABRIC.



STEP 2. MEASURE FROM THE SHOULDER TO THE CUFF

BEGINNING AT THE TOP OF THE ARMHOLE SEAM (AT THE MIDDLE POINT OF THE SHOULDER) MEASURE STRAIGHT DOWN THROUGH THE MIDDLE OF THE SLEEVE TO THE SLEEVE EDGE.

HOW TO MEASURE

THE JACKET'SLENGTH



STEP 1. LAY THE JACKET OUT


LAY THE COMPLETELY BUTTONED JACKET FLAT ON A TABLE FACE DOWN WITH THE COLLAR UP AND ARMS POSITIONED DOWNWARD.

USE YOUR HANDS TO GENTLY EXTEND AND FLATTEN OUT EXCESS FABRIC.



STEP 2. MEASURE FROM THE COLLAR TO THE HEM

BEGINNING AT THE CENTER OF THE COLLAR BASE (WHERE THE JACKET'S BACK SEAM MEETS THE COLLAR), MEASURE TO THE BOTTOM HEMLINE.



ONE LAST NOTE!!!

BE SURE TO MEASURE ACROSS AT THE WIDEST POINT AND AVOID ANY SLACK ON THE MEASURING TAPE.

THE TAPE MUST LAY FLAT ON THE GARMENT.