

# 

HITEK MENSWEAR

## HOW TO MEASURE

### THE WAIST WIDTH



#### STEP 1. LAY THE TROUSERS OUT

LAY THE TROUSERS FLAT, COMPLETELY BUTTONED AND THE ZIPPER ZIPPED UP. THE PANTS MUST BE FACE UP ON THE TABLE.

USE YOUR HANDS TO GENTLY EXTEND AND FLATEN THE FABRIC SO THERE ARE NO WRIPPLES OR WRINKLES.



### STEP 2. MEASURE AND MARK

MEASURE THE WAISTBAND FROM THE TOP EDGE DOWN 1 CM OR ½ INCH POINT. NOTE AND KEEP THAT POINT.



STEP 3. MEASURE ACROSS THE WAISTLINE

STARTING AT THE LEFT EDGE, MEASURE THE TROUSER AT THE 1CM, ½ INCH POINT MARK NOTED IN STEP 2.

HOLD THE TAPE AT THAT POSITION AND THEN TAKE THE TAPE AND FOLLOW THE WAISTBAND LINE ALL THE WAY ACROSS TO THE RIGHT SIDE FOLLOWING THE CURVE OF THE WAISTBAND.

DO NOT MEASURE STRAIGHT ACROSS.

#### HOW TO MEASURE

### THE INSIDE LEG



### STEP 1. LAY THE TROUSERS FLAT ON THEIR SIDE

LAY THE TROUSERS FLAT, COMPLETELY BUTTONED AND THE ZIPPER ZIPPED UP. THE PANTS MUST BE FACE UP ON THE TABLE.


USE YOUR HANDS TO GENTLY EXTEND AND FLATEN THE FABRIC SO THERE ARE NO WRIPPLES OR WRINKLES.



## STEP 2. SPLIT THE LEGS

FOLD THE TOP LEFT ABOVE THE WAISTBAND, EXPOSING THE CROTCH SEAMS.

USE YOUR HANDS TO GENTLY EXTEND AND FLATTEN THE FABRIC.



### STEP 3. MEASURE FROM THE CROTCH TO THE CUFF

BEGIN WHERE THE LEFT AND RIGHT INSEAMS MEET, MEASURE DOWNWARD ALONG THE INSEA TO THE EDGE OF THE HEM.

#### HOW TO MEASURE

#### THE FOOT OPENING




#### STEP 1. LAY THE TROUSERS OUT

LAY THE TROUSER HEM FLAT ON A TABLE. USE YOUR HANDS TO GENTLY EXTEND AND FLATTEN OUT THE FABRIC.



STEP 2. MEASURE THE HEM

MEASURE THE LENGTH ACROSS THE HEM.



ONE LAST NOTE!!!

BE SURE TO MEASURE ACROSS AT THE WIDEST POINT AND AVOID ANY SLACK ON THE MEASURING TAPE.

THE TAPE MUST LAY FLAT ON THE GARMENT.